**Model No: SR-50KG**
Standard Plastics Dryer

Well-distributed Heated Wind: The heat efficiency is high enough to shorten great amount of drying time

Save Time and Manpower. As the hopper body and bottom are designed separately, and therefore it is very convenient to clean materials and quite simple and quick to renew materials as well. A, L feet frames, reciever of hot air, the filter of inlet of fan, the filter ofair exhauster, magnetic base, magnetic iron of bunker, European material box are available for selection.

Features:

- Precise Temperature Controls: The precise temperature controls ensure and keep a high accuracy of temperature
- The Trustworthy Design: Fineexterior, solid construction. Short material-melting time greatly helps to promote the spouting speed
- Increase injection ratio: direct heating blanking, shorten material melt time, promote injection ratio.
- Automatic control time: setting on/off freely 24 hours around, automatic working

**Model No: SR-50KG**

Standard Plastics Dryer

Technical Parameters

| Model | Diameter | External Size | Capacity | Heater Power | Applicable Injectioner |
|---|---|---|---|---|---|
| | Mm | Mm | Kg | Kw | oz. |
| SR-12KG | Ø280 | 640x430x780 | 15 | 2.1 | 1 |
| SR-25KG | Ø350 | 760x500x900 | 25 | 3.5 | 3 |
| SR-50KG | Ø430 | 840x540x1030 | 50 | 4.8 | 5-8 |
| SR-75KG | Ø468 | 950x600x1140 | 75 | 5.1 | 6-9 |
| SR-100KG | Ø550 | 1080x700x1250 | 100 | 7.8 | 10-30 |
| SR-150KG | Ø630 | 1120x760x1300 | 150 | 8.88 | 15-30 |
| SR–200KG | Ø700 | 1250x850x1480 | 200 | 10 | 30-60 |
| SR-300KG | Ø750 | 1300x920x1740 | 300 | 15 | >60 |
| SR-400KG | Ø800 | 1400x1040x1760 | 400 | 20 | >60 |
| SR-600KG | Ø990 | 1600x1150x2150 | 600 | 27 | >60 |
| SR-800KG | Ø1090 | 1700x1330x2660 | 800 | 30 | >60 |
| SR-1000KG | Ø1090 | 1700x1330x2860 | 1000 | 32 | >60 |
| SR-1500KG | Ø1300 | 2100x1400x3000 | 1500 | 48 | >60 |